

TRIPLE POWER

- Safest LiFePO₄ battery
- 90% DOD
- Cycle life > 6000 times
- IP55 protection level
- Floor or wall mounting
- Less self consumption
- Quick installation
- No toxic heavy metals or caustic materials



T-BAT SYS-HV Configuration List

T-BAT H 5.8

Nominal Voltage [V]	115.2
Operating Voltage [V]	100-131
Battery Type	Li-on (LFP)
Nominal Capacity [kWh]	5.8
Faradic Charge Efficiency [%]	99
Battery Roundtrip Efficiency [%]	95
Standard Power [kW]	2.9
Max Power [kW]	4.0
Recommend Charge/Discharge Current [A]	25
Max Charge/Discharge Current [A]	35
Cycle Life [90% DOD]	>6000 Cycles
Warranty [Year]	10
Available Operating Temperature Range [C]	0 to 55
Full-load Operating Temperature Range [C]	5 to 48
Humidity [%]	4 to 100 (condensing)
Altitude [m]	Below 2000
Protection	IP55
System to Inverter	CAN2.0
Battery to Battery/BMS	RS485
Data Collection Port /FW UPDATE	CAN2.0
Master Control Working Mode Indicator	1 LED
Master Control Capacity Indicator	4LED (25%, 50%, 75%, 100%)
Battery Module LED	2 LED
Reset	Button
Switch ON/OFF	Button*1 + breaker*1
Safety	CE, RCM, TUV(IEC62619) UL1973,ROHS,REACH
UN Number	UN3840
Hazardous Materials Classification	Class 9
Transport Testing Requirement	UN38.3
Dimensions(LxWxH) [mm]	474*193*708 (T-BAT H 5.8) / 474*193*647 (HV11550)
Weight [kg]	72.2 (T-BAT H 5.8) / 68.5 (HV11550)

*The Triple Power battery could be scalable up to 4 modules, for a total of 23.2kWh.